XPANDASTORE INSULATED



Assembly Instructions



Insulated Store

Assembly Instructions

General assembly instructions

- Read instructions thoroughly before commencing assembly
- For best results assemble on level, solid ground or it may affect alignment of the wall and ceiling panels
- On initial assembly, hand tighten all nuts and bolts then once full assembly has been completed, tighten again with socket/spanner
- Keep all components and packaging if you plan to demount, move and reassemble in new location

The tools you will need

- 13mm spanner
- 19mm spanner
- Socket set including 13mm and 19mm sockets
- Screw driver

Safety notes

Please review all safety implications before commencing installation including suitability of desired location, local hazards, access and personnel involved in assembly. If in any doubt refer to your company's Health & Safety officer or seek professional advice. Due care should be taken when lifting, assembling and demounting the unit.

General notes after assembly

- Once assembled, the unit can be lifted and re-positioned using a fork lift or crane
- For demounting and relocating in flat-pack condition, using the original packaging is recommended

Terms explained

- Capture nuts This refers to nuts that are pre-attached to the component.
- Chassis The main floor component
- Hand tighten Tightened by hand so secure to hold in place but loose enough to allow for small movement
- Demounted When the unit is disassembled and returned to its original flat-packed state



BEST PRACTICE

To protect your hands, we advise that strong safety gloves are worn while assembling your unit

HOW MANY PEOPLE ARE NEEDED?

Best practice is as follows:

- 2m store 2 people
- 3m store 3 people
- 4m store 4 people





Remove the travelling brackets by unscrewing the 4 bolts using a 19mm socket spanner.





Lift off the roof section and place away from chassis so you have room to work.





Cut the straps and remove the components and panels, avoiding damaging the locating pins that protrude from the bottom of the wall panels.Discard the packaging and packing blocks.





Position the floor chassis in the desired location and don't forget to plan where you want the door to be positioned. Install the first corner post by slotting it into the floor chassis and fixing it in place with x2 bolts and washers using a 13mm socket spanner.







Install the side wall panel by lifting it into place and aligning the 5 locating pins with the holes in the floor chassis. The panel will slot into the recess in the corner post.



HANDY TIP – Temporarily install the 3-pronged L shaped bracket to secure the wall panel to the corner post while you move to the next step.





Install the corner post to secure the other end of the long wall panel. Use x2 13mm bolts and washers.





Install the end panel (the one without the door) by slotting it into place and aligning the locating pins into the holes in the floor chassis. The panel will slot into the recess on the corner post. Don't forget to remove the 3pronged L shaped bracket while you install the panel.







Once in place, install the 3-pronged L shaped bracket by aligning it with the holes in the top corners of the panels (no fixings required).





Now install the next corner post to secure the other end of the short wall panel you have just installed.

Use x2 13mm bolts and washers.





Install the other side wall panel by lifting it into place and aligning the 5 locating pins with the holes in the floor chassis. The panel will slot into the recess in the corner post.





Install the 3-pronged L shaped bracket by aligning it with the holes in the top corners of the panels NOTE: Do not install the last corner post yet







Install the end wall/door panel by lifting it into place and aligning the 3 locating pins with the holes in the floor chassis. The panel will slot into the recess in the corner post. Install the 3-pronged L shaped bracket by aligning it with the holes in the top corners of the panels (no fixings required).



Install the last corner post to secure the wall panels in place using x2 13mm bolts and washers. Install the 3-pronged L shaped bracket by aligning it with the holes in the top corners of the panels (no fixings required).



Install the cylinder locks by sliding it into place. Ensure the key aperture is facing outside and use x1 screw to secure in place.









Install the handles by aligning them with the predrilled holes. Use x2 screws, washers and nuts.





Install the roof section by lifting it and sliding it into place. The panel is designed to sit over the 4 wall panels and its weight will hold the 3-pronged L shaped brackets in place.





Install the lifting eyes and clips which will secure the roof in position. Align the L shaped bracket and lifting eye bracket then secure using x3 13mm bolts and washers in each corner.









Install the long L profiled corner brackets to the inside of the unit. Slide them up to the corner where the roof meets the wall and then slot into the floor chassis. No fixings are required.





Now's the time to check all the bolts are firmly tightened.



Unless already removed, peel off the protective covering. Use a sharp knife to gently cut around each wall panel and peel away diagonally.



Congratulations!

Your Insulated XPandaStore is now fully assembled and ready to use.



XPANDASTORE INSULATED

Accessories

Your Insulated XPandaStore is now ready for use but don't forget, we also have a wide range of handy accessories that you can personalise your units around your own specific needs:

Cable / Hose Holder

An easy to fit bracket for storing cables and hoses etc.

Door Closer

The Ryobi door closer is of sturdy construction and easy to install. Closes door slowly and safely thanks to its hydraulic action.

Levelling Feet

Forklift Feet

Locking Bar













Shelf Arms

Shelf Uprights

Linking Kit

Enlarge your building end to end or side by side

Storage Bins

Made from galvanised steel, storage bins are tough and a great way to safely store a variety of items.

Sump Shelf Available in 1m and 1.9m lengths

Touch Up Spray













Long SIde Linking Kit



For more information or to buy on-line visit www.pandabuildings.com

NOTES



XPandaStore - Flat-packed storage unit



XPandaStore Insulated - Insulated storage unit



XPandaOffice - Flat-packed office/ accommodation unit



XPandaChem - Flat-packed storage unit for the safe storage of chemicals and lubricants



XPandaCabin - Flat-packed office unit home and commercial use



XPandaBikestore - Flat-packed secure storage unit for cycles, motorcycles and tools

The XPandaRange of flat-packed buildings are available from:



King Arthurs Court, Charing, Kent, TN27 0JSI Phone: 01795 810 249 Email: pandabuildings@mail.com www.pandabuildings.com