



XPandaStore Insulated

Floor

Pre-fitted 18mm grade 3 'OSB floor covering, screwed to a galvanised steel chassis frame.

Chassis

The chassis is constructed from a combination of Galvanized U and C channel steel profiles.

Walls

Panels are composed of outer and inner skin 0.40mm thick, painted with 5 micron primer, 20 micron finishing coat galvanized steel sheet , 40 mm thick polyurethane insulation. Outer skin is finished in RAL 6005 Moss Green, inner skin is RAL 9002 Off-White.

Roof

Panels are composed of outer and inner skin 0.40mm thick, painted with 5 micron primer, 20 micron finishing coat galvanized steel sheet , 40 mm thick polyurethane insulation. Outer skin is finished in RAL 6005 Moss Green, inner skin is RAL 9002 Off-White.

Door Panel

0.6 mm corrugated galvanized steel panel. Single door mounted into a steel frame with stainless steel hinges, complete with two deadlocks and replaceable Euro cylinders, door handle fixed to the inner and outer door leaf. The door is insulated with glasswool insulation

Lifting Hooks

4 lifting hooks bolted to corners of the roof

PART WEIGHTS (kg)				
PART	PCS	4 m	3 m	2 m
FLOOR PANEL	1	154	120	89
ROOF PANEL	1	126	102	77
SIDE PANEL	2	74	55	37
REAR PANEL	1	38	38	38
DOOR PANEL	1	67	67	67
OUTER CORNER	4	5,5	5,5	5,5
INNER CORNER	4	1,3	1,3	1,3
HOOK	4	1,4	1,4	1,4
CORNER ADAPTOR	4	0,07	0,07	0,07
TOTAL WEIGHT (kg)		567	471	379

4 m FLAP PANEL	1	94 kg
3 m FLAP PANEL	1	72 kg

PANDA BUILDINGS

